Defom 6500

Defoamer

GENERAL INFORMATION

Defom 6500 is a bubble releasing, anti-foaming agent for solvent based coatings.

CHEMICAL & PHYSICAL PROPERTIES

Composition	modified polysiloxane
Appearance	colorless to slight yellow
	clear liquid
Non-volatile content	0.85 - 1.05 %
Solvent	cyclohexanone
Specific gravity	0.92 - 0.96
Refractive index	1.443 - 1.453 (25 °C)
pH Value	7.0

These are typical properties not to be used for specification purposes.

APPLICATIONS

- Solvent-based coatings
- Solvent-free epoxy coatings

KEY PROPERTIES

- To prevents foaming of solvent based coatings caused by mechanical force such as mixing, production and application.
- To exhibits excellent anti-foaming function in dipping coatings.

INCORPORATION

Incorporated before grinding or processing to achieve optimum effect.

Where post-addition is necessary, it is recommended to incorporate Defom 6500 with sufficient mixing.

LEVELS OF USE

0.1 - 1.0 % based on total formulation.

HEALTH AND SAFETY

As it contains solvents, the product requires special care in handling.

Avoid any eye and skin contact.

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

We recommend to use plastic material as the container to avoid product contamination or affect the quality.

STORAGE RECOMMENDATIONS

Keep away from sources of ignition and heat, as well as container tightly closed in a dry and well-ventilated place.

Stored between 0 °C to 40 °C.

SHELF LIFE

Defom 6500 has a shelf life of 18 months from date of manufacture.

QUALITY ASSURANCE

Quality system at the site manufacturing this product complies with and is certified to ISO 9001 quality standards.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2022, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Trademark of Elementis Specialties, Inc.

North America Elementis 469 Old Trenton Road East Windsor NJ 08512, USA Tel.: +1 609 443 2500 Fax: +1 609 443 2422 Europe

Elementis UK Ltd. c/o Elementis GmbH Stolberger Strasse 370 50933 Cologne, Germany Tel.: +49 221 2923 2066 Fax: +49 221 2923 2011

www.elementis.com

V01 Jul. 2022

Asia Deuchem (Shanghai) Chemical Co., Ltd. 99, Lianyang Road Songjiang Industrial Zone Shanghai, China 201613 Tel.: +86 21 5774 0348 Fax: +86 21 5774 3563

Enhanced Performance Through Applied Innovation