

DeuWax FA-115

Wax Dispersion

GENERAL INFORMATION

DeuWax FA-115 is a unique matting wax dispersions with exceptionally matting as well as slip enhanced effect to the paint films.

CHEMICAL & PHYSICAL PROPERTIES

Composition	polyethylene wax
Appearance	white flowable paste
Non-volatile content	14 - 16 %
Solvent	toluene
Specific gravity	ca. 0.88

These are typical properties not to be used for specification purposes.

APPLICATIONS

- Leather finishes
- N / C lacquer
- Lacquer
- PU
- Solvent-based inks

KEY PROPERTIES

- Are used as stir-in flatting agents. Incorporation is done by simply mixing them during the letdown stage.
- Exhibit outstanding suspending property. Sedimentation or settlement which usually occurs in conventional silica matting agent is not found with these two products.
- Improve smooth, transparent, lubricating and silky feeling surfaces.
- Paint films with additions of **DeuWax FA-115** show superior mar resistance when scratched by fingernails.
- Non-yellowing performance.

INCORPORATION

A combination of **DeuWax FA-115** with silica is recommended for the highest matting effect.

Use a high-speed mixer to incorporate **DeuWax FA-115** into a mixture of solvent and binder.

LEVELS OF USE

10 - 15 % based on total formulation for semi-gloss.

HEALTH AND SAFETY

This product's thixotropy is very high, viscosity may be nonuniform in storage, but is normality. Be sure to stir it before use, and make it run out as far as possible.

The product should be tightly closed, otherwise it would appearance crusting or dry up, please remove it, in order to get the good results.

As it contains solvents, the product requires special care in handling.

Avoid any eye and skin contact.

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

STORAGE RECOMMENDATIONS

Keep away from sources of ignition and heat, as well as container tightly closed in a dry and well-ventilated place.

Stored between 0°C to 40°C (use after return to 25°C).

Packaging not to be exposed direct heat radiation.

DeuWax FA-115

SHELF LIFE

DeuWax FA-115 has a shelf life of 12 months from date of manufacture.

QUALITY ASSURANCE

Since 1992 the company is a holder of the ISO 9001 / ISO 9002 certificates, which guarantees that all operations are conducted according to the stipulated standards.

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2018, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

© Trademark of Elementis Specialties, Inc.

V01 Feb. 2018

North America

Elementis
469 Old Trenton Road
East Windsor
NJ 08512, USA
Tel.: +1 609 443 2500
Fax: +1 609 443 2422

Europe

Elementis UK Ltd.
c/o Elementis GmbH
Stolberger Strasse 370
50933 Cologne, Germany
Tel.: +49 221 2923 2066
Fax: +49 221 2923 2011

Asia

Deuchem (Shanghai) Chemical Co., Ltd.
99, Lianyang Road
Songjiang Industrial Zone
Shanghai, China 201613
Tel.: +86 21 5774 0348
Fax: +86 21 5774 3563