

## Levaslip 879

### Leveling Agent

#### GENERAL INFORMATION

**Levaslip 879** is a slip and leveling agent. It provides excellent slip performance.

#### CHEMICAL & PHYSICAL PROPERTIES

Composition	modified polysiloxane
Appearance	colourless to slight yellow, clear to slight hazy viscous liquid
Non-volatile content	≥ 94 %
Specific gravity	1.01 - 1.04
Reflective index	1.443 – 1.448 (25 °C)

These are typical properties not to be used for specification purposes.

#### APPLICATIONS

- non-aqueous
- 2K PU
- N / C lacquer
- A / C lacquer
- waterborne coatings

#### KEY PROPERTIES

- Excellent slip performance.
- Lower surface tension, improves substrate wetting.
- It can be reduce coefficient of friction and improve scratch resistance.
- Good compatibility in various non-aqueous coatings.
- If need to re-coat, please test recoatability.

#### INCORPORATION

For easy to use, please pre-dilute **Levaslip 879** before use.

#### LEVELS OF USE

0.1 - 0.5 % based on total formulation. It is recommended to carry out serial test of Levaslip 879 at various levels to obtain optimum dosage.

#### HEALTH AND SAFETY

The product requires special care in handling. Avoid any eye and skin contact.

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

#### STORAGE RECOMMENDATIONS

Keep away from sources of ignition and heat, as well as container tightly closed in a dry and well-ventilated place.

Stored between 0 °C to 40 °C.

Before using this product please consult our Safety Data Sheet (SDS) for information on safe handling and storage. The SDS can be found on the company website.

#### SHELF LIFE

**Levaslip 879** has a shelf life of 2(two) years from date of manufacture.

#### QUALITY ASSURANCE

Quality system at the site manufacturing this product complies with and is certified to ISO 9001 quality standards.

*NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.*

© Copyright 2022, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

© Trademark of Elementis Specialties, Inc.

V01 Jul. 2022

##### North America

Elementis  
469 Old Trenton Road  
East Windsor  
NJ 08512, USA  
Tel.: +1 609 443 2500  
Fax: +1 609 443 2422

##### Europe

Elementis UK Ltd.  
c/o Elementis GmbH  
Stolberger Strasse 370  
50933 Cologne, Germany  
Tel.: +49 221 2923 2066  
Fax: +49 221 2923 2011

##### Asia

Deuchem (Shanghai) Chemical Co., Ltd.  
99, Lianyang Road  
Songjiang Industrial Zone  
Shanghai, China 201613  
Tel.: +86 21 5774 0348  
Fax: +86 21 5774 3563